

Fast and efficient

imageRUNNER
1730i, 1740i and 1750i

you can

Compact and space saving, these high-speed A4 devices are ideal for busy offices. Productive multifunctional capabilities save time while cost saving features help you save money too.

30-50 PPM / CPM, A4 B&W
SCAN TO EMAIL AND FOLDER
UP TO 2,300 SHEET CAPACITY
5.7 INCH / 14.47cm QVGA TILT LCD TOUCH DISPLAY
ENERGY EFFICIENT
COMPACT DESIGN



The image shown above is the imageRUNNER 1750i

Productivity and efficiency.

- Easy-to-use tiltable touch-screen display
- Fast print speeds up to 50ppm
- Send in colour to a network folder or email in a variety of formats
- Fewer interruptions with up to 2,300 sheet paper capacity
- Optional compact staple finisher
- Simple, hassle-free integration - Network ready, PCL and PostScript Support.
- Compatibility with Canon's e-Maintenance service offers remote diagnostics, automated meter readings and consumables monitoring

Environmental.

- Energy Star certified and low TEC rating
- Consumes as little as 1 watt in sleep mode
- Automatic double-sided output

Cost Effective.

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance

Security .

- Secure Print* keeps documents confidential during printing
- Department ID secures access to the device
- uniFLOW compatibility offers the flexibility and convenience of My Print Anywhere secure release with job selection

* RAM-based secure print for up to 100 jobs

imageRUNNER

Canon

Specifications: imageRUNNER 1700 series

imageRUNNER 1700 series	
Machine Type	Mono Laser Multifunctional.
Available Core functions	imageRUNNER 1730i: Print, Copy, Scan, Send and Optional Fax imageRUNNER 1740i: Print, Copy, Scan, Send and Optional Fax imageRUNNER 1750i: Print, Copy, Scan, Send and Optional Fax
PRINTER SPECIFICATIONS	
Print speed	imageRUNNER 1730i: Up to 30 ppm (A4) imageRUNNER 1740i: Up to 40 ppm (A4) imageRUNNER 1750i: Up to 50 ppm (A4) Monochrome laser beam printing 600 x 600 dpi, Up to 1200 x 1200 dpi (Enhanced) Automatic
Printing method	Supported memory media: USB memory key
Print Resolution	Supported file types: JPEG, TIFF
Double sided printing	550-sheet paper cassette
Printing from memory media	100-sheet multi-purpose tray
Paper input (Standard)	3 x 550-sheet cassettes
Paper input (Option)	2300 sheets
Maximum paper input capacity	250-sheets (80gsm)
Paper output capacity	Standard: Group
Finishing capabilities	Optional Stapler: Collate, Group, Staple
Supported media types	Finisher: Plain paper, Recycled paper, Colour paper, Heavy paper, Punch, Envelope*
	*Envelope support via drawer 2 only. Requires optional Envelope Cassette-D1
	Multi-purpose tray: Plain paper, Recycled paper, Colour paper, Heavy paper, Punch, Bond, Transparency, Label, Envelope (No.10 (COM10), ISO-B5, Monarch, ISO-C5, DL)
Supported media sizes	Paper Drawer 1, 3 and 4: Standard size: A4, A5, B5, Legal, Letter, Executive, STMT (COM10), ISO-B5, Monarch, ISO-C5, DL) Paper Drawer 2: Standard size: A4, A5, B5, Legal, Letter, Executive, STMT, Envelopes* (No.10 (COM10), ISO-B5, Monarch, ISO-C5, DL) *Requires optional Envelope Cassette-D1
	Multi-purpose tray: Standard size: A4, A5, B5, Legal, Letter, Executive, STMT, Free size (99 mm to 216 mm x 140 mm to 356 mm), Envelopes (No.10 (COM10), ISO-B5, Monarch, ISO-C5, DL)
Supported media weights	Cassette/s: 64 to 105 g/m ²
Printer Language(s)	Multi-purpose tray: UFR-II-LT (Standard) PCL5e/6 (Standard) PostScript Level 3 Emulation (Standard)
Fonts	PCL fonts: 93 Roman PS fonts: 136 Roman
Operating system compatibility	UFR-II-LT: Windows® 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2 PS: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later), MAC OS 9.1 or later, MAC OS X (10.2.8 or later) PPD: Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7
	Please refer to http://software.canon-europe.com for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place
COPY SPECIFICATIONS	
Copy speed	imageRUNNER 1730i: Up to 30 cpm (A4) imageRUNNER 1740i: Up to 40 cpm (A4) imageRUNNER 1750i: Up to 50 cpm (A4)
First Copy Output Time (FCOT)	Approx. 5 seconds or less

Copy resolution	Up to 600 x 600 dpi
Multiple copy	Up to 999 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	Collate (requires Finisher), 4 on 1, ID Card Copy
SCAN SPECIFICATIONS	
Optional/Standard Type	Standard on all models Colour Flatbed and Duplex Automatic Document Feeder (DADF)
Supported media size/s	A4, A5, Legal, Letter, Custom sizes (W x L): Max 216 mm x 356 mm Min. 140 mm x 140 mm
Supported media weight/s	Single-sided: 42 to 128 g/m ² Double-sided: 50 to 128 g/m ²
Scan resolution	up to 600 x 600 dpi in Black and White up to 300 x 300 dpi in Colour
Double sided scanning	2-sided to 2-sided (Automatic)
Scan speed	Mono Single-sided: imageRUNNER 1730: 30ipm/ A4(600dpi/300dpi) imageRUNNER 1740/1750: 50ipm/A4(600dpi/300dpi) imageRUNNER 1730: 20ipm/A4(600dpi/300dpi) imageRUNNER 1740/1750: 32ipm/A4(600dpi/300dpi) imageRUNNER 1730: 30ipm/A4(300dpi) imageRUNNER 1740/50: 50ipm/A4(300dpi) imageRUNNER 1730: 20ipm/A4(300dpi) imageRUNNER 1740/50: 32ipm/A4(300dpi)
Scan methods	Push Scan: Send functionality available on all models. Pull Scan: TWAIN/VIA Pull scanning available on all models Yes available on all models
Pull scan specifications	Scan to USB Memory Key: TWAIN Via Network TWAIN Driver Supported OS: Windows 2000/ Windows XP/ Windows Server 2003/ Windows Vista/ Windows Server 2008/ Windows 7 (32 bit, 64 bit in compatibility mode)
SEND SPECIFICATIONS	
Pull scan specifications	Standard on all models up to 600 x 600 dpi in Black and White up to 300 x 300 dpi in Colour
Destinations	E-Mail/ Internet FAX (SMTP), PC(SMB, FTP)
Address Book /	LDAP (1000) / Local (Max. 500)
Speed dials	TIFF (B&W), JPEG, PDF, PDF (Compact), Optional
File formats	Searchable PDF
Universal Send	No
Feature Sets	
FAX SPECIFICATIONS	
Optional/Standard	Optional on all models
Modem Speed	Super G3 33.6kbps (Up to 3 seconds/page ¹)
Fax Resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
Fax Memory	Up to 1000 pages ¹
Speed Dials	Max. 500
Group Dials/	Max. 499 dials
Destinations	Max. 500 address + New 32 destinations
Sequential Broadcast	1 hour
Memory backup	Fax Forwarding, Dual Access, PC Fax (TX only)
Other features	
GENERAL SPECIFICATIONS	
Warm-up Time	Approx. 30 seconds or less from power on
Interface type	USB 2.0 Hi-Speed 10BASE-T/100BASE-TX 1 x USB Host (2.0)- Rear of device Optional 3 Port USB Host (2.0) hub- Side of device
Network protocols	TCP/IP (LPD/ Port 9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support
Processor Speed	400 Mhz
Memory	512 MB (shared)
Hard Disk Drive	No (RAM-based Secure Print standard)
Control panel	5.7 inch monochrome touchscreen tiltable LCD display
Dimensions (W x D x H)	560 mm x 500 mm x 633 mm
Installation space (W x D)	787 mm x 960 mm 1182 mm x 960 mm (Full configuration including staple finisher)

Weight	Approx. 44.3kg (excluding toner)
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz)
Power Consumption	Maximum: Approx. 1600 W Standby: Approx. 43 W or less Energy Saver Mode: Approx. 8.5W or less Sleep mode: Approx. 1 W or less Sound Pressure ² Active: IR1730i 69.5 dB or less IR1740i 73.0 dB or less IR1750i 75.0 dB or less
Noise Levels	Standby: IR1730i 43.0 dB or less IR1740i 53.0 dB or less IR1750i 53.0 dB or less
Software and printer management	IWMC - Centralised management of the device eMaintenance compatibility- enables Meter reading, Automatic consumables management and remote diagnostics Network ScanGear NetSpot Device Installer Remote User Interface (RUI) Department ID Management uniFLOW Login Device Client - Embedded uniFLOW Compatibility
Security Features	IP/ Mac Address Filtering, Department ID, Secure Print (RAM-based), My Print Anywhere secure print with Job Selection via uniFLOW (Option)
CONSUMABLES	
Toner Cartridge/s	C-EXV37 TONER (15,100 pages ³)
SPECIFICATIONS FOR OPTIONS	
Staple Finisher	Name: Staple Finisher-H1 Number of Trays: 1 Stack Capacity: With stapling: 20 sets. Without stapling: 500 sheets Maximum Stapling capacity: Up to 50 sheets Paper Weight: 64 to 128 g/m ² Staple Position/s: Single (Top-Left) Dimensions (W x D x H): 798 mm x 395 mm x 263 mm Weight: Approx. 10.5 kg
Cassette Feeding units	Name: Cassette Module-Y1 Dimensions (W x D x H): 540 mm x 500 mm x 158 mm Weight: Approx. 7.7 kg
ADDITIONAL OPTIONS	
Additional Options	Cassette Module-Y1: Additional 550-sheet cassette Envelope Cassette-D1: enables envelope feeding in paper drawer 2 Staple Finisher-H1: Compact stapler finisher Barcode Print Kit-B1: Provides Barcode printing capability using Jet Caps technology Super G3 Fax Board-A1: Adds fax functionality Color Send Searchable PDF Kit-E1: Searchable PDF option for Send functionality Canon Copy Card Reader-F1: Physical card access system that limits access to authorised users Copy Card Reader Attachment-C1: Attachment kit for Card Reader-F1 or for uniFLOW MiCARD reader as the bracket USB Application 3-Port Interface Kit-B1: 3-Port USB interface kit for USB memory ADF Access Handle-A1: Attaches to the document feeder, making access easier for seated users FL Cassette-AP1: Spare 550-sheet paper tray for all cassettes Plain Pedestal (Higher-type): The pedestal can be placed under the standard/optional cassette module to raise the device when free-standing Plain Pedestal (Lower-type): The pedestal can be placed under the standard/optional cassette module to raise the device when free-standing
FOOTNOTES	
[1] Based on ITU-T Standard Chart No. 1	
[2] Declared noise emission in accordance with ISO 7779	
[3] Based on 6% coverage	
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. TM and © All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Microsoft, Windows and Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.	



Canon UK
canon.co.uk

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2011

Canon (UK) Ltd
Woodhatch
Reigate, Surrey
RH2 8BF UK

Tel: 01737 220000
Fax: 01737 220022
www.canon.co.uk

Canon Ireland
3006 Lake Drive
City West, Saggart
Co Dublin

Tel: 01 2052400
Fax: 01 2052525
www.canon.ie